

TW1004BP



Subwoofer Amplifier

Class AB: 100W

FEATURES

- RMS 100W, 4 ohm High Power Output
- Line Voltage 115/230 vac Switchable
- Anti-Clipping Circuit to Reproduce Clear Base Sound
- Over Load Protection Circuit
- Phase Control Switch
- Auto-On Switch
- Volume Control
- Variable Crossover Control
- Base Equalization Circuit
- Line Level Input (R, L)
- Line Level Output (R, L)
- Speaker Level Input (R, L)
- Speaker Level Output (R, L)
- Twin Color LED Indicator for Signal ON/OFF

CE & ETL APPROVAL FILE NO.:
ETL: CT2110
EMC: EME-020682
LVD: ETS-02265



TW1004BP--100W
4 ohm, 115/230 vac, BP type, class AB

SPECIFICATIONS

- Output Power Into 4 Ohm Load 100w RMS
- T.H.D. < 1%
- Volume Control Range > 70dB
- Phase Control 0°~180°
- Crossover Frequency Adjust Range 40~140Hz
- Number of Pole for Crossover Frequency 2 Pole
- Bass EQ Frequency Boost Level 32 Hz/+5dB
- Auto Turn-On Level 3 mV
- Time to Stand-by 10~15 min
- Max. Sensitivity of Line Level Input 80 mV
- Max. Sensitivity of Speaker Level Input 2 V
- Dimension of Front Panel 254 x 254 (mm)

TW Series
Subwoofer Amplifier
MODEL: TW1004BP-AB

TW1004BP

ELYTONE ELECTRONIC CO., LTD.

Office: 9, Lane 210 Wen Chang St., Taipei 106, Taiwan
Tel: 886 2 2671 2071 Fax: 886 2 2672 3775 Email: salesdept@elytone.com.tw

Website: www.elytone.com.tw